

DIRT REPELLENT

TEXTURED PORCELAIN TILES, UNPOLISHED
PORCELAIN TILES, LAPPATO PORCELAIN TILES



WHAT IT'S FOR

- Makes cleaning quick and easy and surfaces hygienic
- Improves the material's resistance to dirt
- Maintains the original appearance of the material over time

ADVANTAGES

- Provides prolonged protection over time
- For interior and exterior use
- High coverage
- Does not alter the material's slip resistance (tests conducted in conformity with B.C.R.A. and ASTM C 1028-2007 methods).
- Does not form surface film
- UV resistant and non-yellowing
- An A+ classified product in accordance with the French VOC regulation

HOW TO USE IT

No dilution required: ready to use.

Application for new installations:

1. Wash the floor thoroughly using **DETERDEK PRO** (cement-based grouts) or **CR10** (epoxy grout).
2. Apply **STOP DIRT** to a clean and dry floor also treating the grout, covering evenly with a fleece or other suitable applicator.

Advice from the expert: Given the product's high coverage, apply a moderate quantity of product to treat 2-3 m² of surface area at a time.

3. Rub the surface with a cloth or single-disc machine with white disc.
4. Fully remove all product residues within 10 minutes, either manually using a microfibre cloth or with a single-disc machine.
5. After at least 12 hours, before treading on the treated surface, remove any product residues using a clean microfibre cloth.

Application on untreated surface to be restored:

1. Wash the floor using **PS87 PRO** and/or **DETERDEK PRO**.
2. Apply **STOP DIRT** on the dry surface in the manner described above.

Caution:

The product may enhance the colour of the material or grouting; carry out a spot test on a small surface area beforehand.

Aerate rooms during use.

Do not apply to matt-finish Lappato porcelain tiles.

*If the product is applied incorrectly, remove **STOPDIRT** using **FASEZERO**.*



PICTURES: by courtesy of Ceramiche Atlas Concorde S.p.a.

COVERAGE

COVERAGE (1 litre):

Textured, natural and Lappato
porcelain tiles **up to 70 m²**

Coverage shown is indicative and refers to single coats

Packaging

500mL: boxes of 12.

WARNINGS

- This is a solvent-based product, the room should be aerated during application.
- Keep out of reach of children.
- Do not disperse into the environment after use.
- The use of a single-disc cleaning machine is permitted only if it is in perfect working condition.

TEMPERATURES

Storage temperature: from 0°C to 30°C

The product should be applied to materials with temperature between 5° and 30°C.